

PRECOTE® 30, 80, 85

Chemical adhesives with assembly-actuated, fast-curing, vibration-resistant locking and sealing properties for a wide range of internal and external fastener applications.



PRECOTE MICROENCAPSULATED pre-applied chemical adhesives are available in several strength grades and are suitable for all metallic fasteners, with many plated surfaces in thread sizes #8 (M4) and larger, and internal diameter sizes 1/4" (M6) and larger.

PRECOTE offers a number of distinct advantages:

- Only thread adhesive with dual microencapsulation to maintain high integrity of chemical components.
- No additional locking devices needed
- Precise thread coverage every time
- Increases productivity at the assembly line
- Exceeds IFI-125 and IFI-525 and most automotive specifications
- Can be applied on external or internal threaded fasteners
- Assembly ready
- Longer shelf life (once coated, **PRECOTE** is unaffected by atmospheric conditions or high humidity)
- Dry-to-touch, non-tacky finish
- Non-toxic, assembler friendly
- Environmentally safe



INNOVATION & PRECOTE.

Innovation is Nylok's word for our way of developing new products that solve challenges our customers are facing.

PRECOTE was introduced in answer to industry's need for a better way of fastening components in place during assembly. It has been approved worldwide by automotive manufacturers and has proved invaluable in electronics, telecommunications, aerospace and other high-tech industries.

It is available in these versions:

- **PRECOTE 30®**: Yellow – For medium thread locking and sealing where lower strength and easy removal are required. Temperature resistant from -58°F to 300°F (-50°C to 150°C). No uncontrolled post-curing.
- **PRECOTE 80®**: Pink – For high-strength thread locking and sealing and heat resistant thread coating. Temperature resistance from -58°F to 340°F (-50°C to 170°C). No uncontrolled post-curing.
- **PRECOTE 85™**: Turquoise – High-strength thread coating for high stressed bolts with controlled torque/tension. Temperature resistance from -58°F to 340°F (-50°C to 170°C). No uncontrolled post-curing.



586.786.0100 Fax 586.786.0598
15260 Hallmark Drive, Macomb, MI 48042

www.nylok.com

PRECOTE 30, 80, 85 meets and exceeds these key industry specifications:

COMPANY NAME	SPECIFICATIONS
GM	GM-6124M
GM	GM-6175M
GM	GM-6194M
Ford	WX200
Ford	WSSM-11PA-A1
Ford	ESS-20007-S100
Ford	ESS-20010-S100
Ford	ESEM-11P2A-A1&2
Ford	W SM-18P-12A
DaimlerChrysler	MSCD76
DaimlerChrysler	PF-6616
Detroit Diesel	9S278
IFI	IFI-125
IFI	IFI-525
IFI	IFI-160
IFI	IFI-560
DIN	DIN-267, PART 27
John Deere	RES-10432
Rockwell International	Q-29
Caterpillar	IE-2486
Allied Signal	WI-504
Bendix	BW621M, BW291P
INTERNATIONAL	SPECIFICATIONS
Land Rover	RES.22.FP.01
British Leyland	BLS 22.FP.01
Burman & Sons	QC-1007
Perkins Diesel	PMS P1.02
VW	601 05
Renault	39.02.010
Peugeot	B 141 230
Citeron	B 141 230
Talbot	B 141 230
Porsche	1230
Daimler-Benz	DBL 8830
BMW	DIN 267 PART 27

If it's new, it's Nylok.

Whether it is developing a new product to satisfy a customer's need, or solving a customer's problem with an existing product, NYLOK engineers are accustomed to meeting challenges head on.

The result is an ever-growing number of patents for products, processes and equipment which continues to lead the field of fastener technology.

Recommendations from Nylok engineers have saved customers thousands of dollars. Many companies have experienced the value of working with us early in the design stage.

How much time and/or money can our kind of innovation save you? Why not find out for yourself by calling us in on your next project?

The earlier, the better.



JUNKER VIBRATION TEST

